

SAFETY DATA SHEET

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product name

Road Repair Asphalt

Supplier

Hanson Cement Ketton Works Ketton Rutland PE9 3SX

Emergency telephone

01780 720501

2 HAZARDS IDENTIFICATION

Not regarded as a health or environmental hazard under current legislation.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification (67/548)
Paving Grade Bitumen	232-490-9	8052-42-4	1-10%	-
Skim Coated Stone	-	_	60-100%	-

The Full Text for all R-Phrases are Displayed in Section 16

Composition comments

The Data Shown is in accordance with the latest EC Directives.

4 FIRST-AID MEASURES

General information

Move into fresh air and keep at rest. Get medical attention if any discomfort continues.

Ingestion

Immediately rinse mouth and provide fresh air. Immediately rinse mouth and drink plenty of water. Keep person under observation. If person becomes uncomfortable seek hospital and bring these instructions.

Skin contact

Remove contaminated clothing. Get medical attention if any discomfort continues.

Eye contact

Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.



SAFETY DATA SHEET

5 FIRE-FIGHTING MEASURES

Extinguishing data

Use: Foam. Powder.

Special fire fighting procedures

Carbon dioxide (CO₂). Water spray, fog or mist.

Unusual fire and explosion hazards

Fire causes formation of toxic gases.

Protective measures in fire

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

6 ACCIDENTAL RELEASE MEASURES

Personal precautions

For personal protection, see section 8.

Environmental precautions

Do not discharge onto the ground or into water courses.

Spill clean up methods

Recover the product and place in a suitable container for reuse.

7 HANDLING AND STORAGE

Usage precautions

Avoid contact with skin and eyes. Avoid eating, drinking and smoking when using the product. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site.

Storage precautions

Store in a cool and well-ventilated place.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA -	8 hrs	STEL -	15 min	Notes
Paving Grade Bitumen	WEL	_	5mg/m³	_	10mg/m³	_
Skim Coated Stone	WEL	_	5mg/m³	_	10mg/m³	-

WEL = Workplace Exposure Limit.

Protective equipment









SAFETY DATA SHEET

Engineering measures

Well-ventilated area.

Respiratory equipment

If ventilation is insufficient, suitable respiratory protection must be provided.

Hand protection

Protective gloves should be used if there is a risk of direct contact or splash. Neoprene or nitrile gloves recommended.

Eye protection

Wear approved safety goggles.

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance Solid

Colour Black

Odour Characteristic

10 STABILITY AND REACTIVITY

Stability

Stable under normal temperature conditions and recommended use.

Conditions to avoid

Avoid heat, flames and other sources of ignition.

Hazardous decomposition products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

11 TOXICOLOGICAL INFORMATION

Skin contact

Repeated exposure may cause skin dryness or cracking.

Eye contact

Irritating to eyes.

12 ECOLOGICAL INFORMATION

Ecotoxicity

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.



SAFETY DATA SHEET

13 DISPOSAL CONSIDERATIONS

General information

Waste to be treated as controlled waste. Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority.

Disposal methods

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION

General

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

15 REGULATORY INFORMATION

Risk phrases

NC - Not classified.

Safety phrases

NC - Not classified.

UK regulatory references

The Control of Substances Hazardous to Health (Amendment) Regulations 2004 Chemicals (Hazard Information & Packaging) Regulations.

Environmental listing

Control of Pollution Act 1974.

EU directives

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

Approved code of practice

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

National regulations

Workplace Exposure Limits 2005 (EH40) The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2007 (CDG 2007).



SAFETY DATA SHEET

16 OTHER INFORMATION

General information

If further information on training is required contact Hanson Cement Ltd.

Revision date

01/11/12

Rev. No./Repl. SDS generated

0

Risk phrases in full

NC - Not classified.

DISCLAIMER

The purpose of the above information is to describe the products only in terms of health and safety requirements. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. It is the users obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date specified.

All goods are supplied in accordance with Hanson Cement Ltd's general conditions of sale, copies of which may be obtained by telephoning sales on 01780 720501

5 OF 5

PE9 3SX

DATE OF ISSUE: NOVEMBER 2015

Hanson Cement Ketton Stamford Lincolnshire

For further information contact:

Tel: 0330 123 2441 Fax: 01780 727154

Technical Helpline:

Tel: 0330 123 2074 Fax: 01780 727008

Customer Services:

Email: cement.technical.help@hanson.biz

Email: cement.customer.services@hanson.biz

>>>>>>>

www.hanson.co.uk