

10mm Gravel

Technical Data Sheet



PACK SIZE

Available in Maxipack and Bulk bags

DESCRIPTION

10mm single-sized gravel aggregate conforming to the requirements of BS EN 12620.

Typical moisture content: 3%

Particle size: 4-10mm

Shell content: ≤ 10%

Chloride content: ≤ 0.01%

Acid soluble sulfate: ≤ 0.8%

USES

In combination with cement, sharp sand and water in suitable mix designs to produce fine concretes.

This product is also suitable for use in concrete for paths, patios, setting posts, steps and also as top dressing for paths and driveways.

PREPARATION AND CONTROL OF CONCRETE

All the constituents should be thoroughly mixed prior to the addition of water. Sufficient water should then be added to give a suitable consistence for placing and compaction. On completion of compaction and finishing the concrete surface, the surface should be covered with sheeting to prevent loss of moisture during curing and to protect from surface damage.

MIX DESIGN

For detailed advice on concrete mixes and their constituent materials please consult BS 8500 Parts 1 and 2. For general guidance refer to www.hanson-packedproducts.co.uk/en/products/cements.

COVERAGE

	Coverage as Fine Concrete Mix	Coverage as Top Dressing
Maxipack bag	App. 0.35m ² @ 50mm depth	App. 0.4m ² @ 50mm depth
Bulk bag	App. 9m ² @ 50mm depth	App. 12m ² @ 50mm depth

TECHNICAL SUPPORT

For further advice please contact Hanson Cement's Technical Helpline on 0330 123 2441.

HEALTH AND SAFETY

Please refer to Material Safety Data Sheet for full information.



For further information contact:

Hanson Cement
Ketton
Stamford
Lincolnshire
PE9 3SX

Hanson-packedproducts.co.uk

Customer Services:

Tel: 0330 123 4525
Email: cement@hanson.com

